

Pre-Fabricated, Reinforced Fiberglass

Easier to Ship and Install Than Concrete Pits

Up to 600 Gallons and 3-Stage Processing

Economical Alternative to Concrete Pits

Water Maze's pre-fabricated fiberglass pits offer an economical solution to in-ground, oil-water separation as well as a safe and convenient method of capturing wash water.

The fiberglass pit system is easier to install and less expensive to ship than forming pits on site or purchasing straight pre-cast pits. Furthermore, they feature double containment to eliminate leaks, offer pre-formed grating and simply look better than concrete or metal pits.


The fiberglass pits must be installed in concrete on all sides. Each pit comes with step-by-step installation instructions.

Once installed, the reinforced fiberglass sidewalls prevent bowing and underground movement. The larger collection pit works best when combined with a catch basin and sump pit, which are also made of the same long-lasting, chemical-resistant, reinforced fiberglass.

The larger collection pit is designed with baffles to force oil to rise and other debris to sink. Also, Water Maze's oil-coalescing plates are designed to fit snugly into the center chamber to enhance separation effectiveness.

Fiberglass Pit Specifications

| Features | 30-710 | 30-714 | 30-715 |
|------------------------|------------------|---------------------|-----------------------|
| Description | Collection Pit | Catch Basin | Catch Basin/Sump Pit |
| Holding Capacity | 600 gal | 159 gal | 47 gal |
| Outside Dimen. (LxWxH) | 119" x 45" x 55" | 46.5" x 46.5" x 58" | 31.25" x 31.25" x 38" |
| Shipping Weight | 302 lbs | 130 lbs | 75 lbs |



AVAILABLE OPTIONS

| Part No. | Description |
|-----------|--|
| 30-720 | Coalescing grid pack 850 sq. ft. (2 required). Enhances oil/water separation when discharging to sanitary sewer |
| 30-721 | Collection pit cover (3' x 9'), hinged aluminum diamond tread plate with steel tube frame (120 lbs shipping weight) |
| 30-722 | Cover (2' x 2') for sump pit, aluminum diamond tread plate with steel tube frame (40 lbs shipping weight). |
| 30-723 | Grating (2' x 2') for sump pit (30-715), hot rolled 1/2" x 2" steel flatbar (190 lbs shipping weight) |
| 30-724 | Grating (1.5' x 3') for catch basin (30-714), hot rolled 1/2" x 2" steel flatbar; set of 2 (270 lbs shipping weight) |
| 2-010048 | 3" Bulkhead fitting, threaded |
| 9-5025 | 4-1/2" hole saw |
| 9-5026 | Arbor for hole saw (7/16"); for installation of bulkhead fitting |
| 4-0422015 | Wood brace kit (specially designed bracing to reinforce fiberglass collection pit while pouring concrete) |
| 30-775 | Strainer, catch basin, stainless steel |

Distributed by:



HPI PROCESSES, Inc.
1030 Revenue Dr., Telford, PA 18969

Phone : 1-215-799-0450
Fax : 1-215-799-0459

Toll-Free : 1-888-733-2832
www.hpipro.com